



COLORS AVAILABLE

- Neutral
- Black
- Blue
- Green
- Yellow
- Red

CHEMICAL RESISTANCE

- Aqueous solutions of acids, lyes and salts
- Organic solvents

APPLICATION

- Compressed air for control technology
- Sampling lines
- Flexible pneumatic lines
- Flexible fuel and lubricant systems
- Environments with high humidity

PROPERTIES

- Good flexibility
- Impact resistant
- Non-toxic
- Good chemical resistance
- Colour black: UV resistant
- Also available: HDPE

Is available on request in other lengths than the standard coil.

TECHNICAL SPECIFICATIONS

Temperature Range °C	-40 to + 80
Material	LDPE

PRODUCT INFORMATION

Size	P	D	d	s	Bending radius	MOQ	kg/100m
4/2x1	21	4.00	2.00	1.00	18.0	100m	1.180
5/3x1	14	5.00	3.00	1.00	20.0	100m	1.470
6/4x1	12	6.00	4.00	1.00	30.0	100m	1.540
6/4x1	12	6.00	4.00	1.00	30.0	250m	1.540
6.35/4.35x1	10	6.35	4.35	1.00	30.0	100m	2.050
8/6x1	8	8.00	6.00	1.00	40.0	100m	2.640
9.52/6.52x1.5	10	9.52	6.52	1.50	40.0	100m	3.000
10/8x1	6	10.00	8.00	1.00	60.0	50m	3.230
10/7x1.5	11	10.00	7.00	1.50	40.0	50m	3.740
12/10x1	6	12.00	10.00	1.00	80.0	50m	4.620
12/9x1.5	9	12.00	9.00	1.50	65.0	50m	4.620
16/13x1.5	6	16.00	13.00	1.50	80.0	50m	7.000

Bar= operating pressure at 23 °C

- MOQ = Minimum order quantity
- P = pressure (bar)
- D = tube outside diameter (mm)
- d = tube inside diameter (mm)
- s = wall thickness (mm)

