



COLORS AVAILABLE

- Neutral
- Black
- Blue
- Gray
- Yellow

CHEMICAL RESISTANCE

- Most oils and greases
- Aliphatic hydrocarbons
- Oxygen
- Ozone

APPLICATION

- Measurement and control technology
- Pneumatics
- Hydraulics
- Machine and motorbuilding

PROPERTIES

- Excellent bending
- Little deformation even with long-term stress
- High cold flexibility
- Abrasion resistant

Also available:

PU tubing for ultraclean application
Cleaned and double packed according to customer specifications

TECHNICAL SPECIFICATIONS

Temperature Range °C	-60 to + 80
Material	PU

PRODUCT INFORMATION

Size	P	D	d	s	Bending radius	MOQ	kg/100m
4/2.5x1	6	4.00	2.50	1.25	8.0	100m	0.940
6/4x1	13	6.00	4.00	1.00	20.0	100m	1.167
8/6x1	10	8.00	6.00	1.00	25.0	100m	3.400
8/5x1	6	8.00	5.00	1.50	15.0	100m	3.770
10/6.5x1	6	10.00	6.50	1.75	22.0	100m	3.650
10/8x1	7	10.00	8.00	1.00	35.0	100m	5.200
12/8x2	6	12.00	8.00	2.00	29.0	100m	5.100

Bar= operating pressure at 23 °C

- MOQ = Minimum order quantity
- P = pressure (bar)
- D = tube outside diameter (mm)
- d = tube inside diameter (mm)
- s = wall thickness (mm)

